



Product Name :
Digital Torque Tester

Product Code :
HND-TEW-0004



Description :

Digital Torque Tester

Technical Specification :

Integral Transducer and sturdy housing allow mounting in virtually any position.

Integral Transducer: Full bridge strain gage, 350 ohm, 1500uE, 3mV/V F.S, 3.75 excitation.

Units of Torque: Nm, kg.cm., ft.lb., in.lb., in.oz.

Audible (tone).

Torque Accuracy: $\pm 0.5\% \pm 1\%$ count CW and CCW from 10% to 100% of full scale at 25° C.

LCD Touch Screen: 4.7 inch color graphics display.

Screen resolution: 480 X 272 pixels.

Display Accuracy: 4 digits, 500 cycle counts.

6 "AA" Alkaline cells for battery power included.

Track, Peak and First Peak modes of operation.

Operating Temperature: 40° to 110° F (5° to 42° C).

Storage Temperature: 0° to 122° F (-20° to 50° C).

Humidity up to 85% non-condensing.

Customized size and specification as per your drawing or sample. We Digital Torque Tester suppliers UAE Dubai, can make the Digital Torque Tester as per your request, specification, size and bulk quality Dubai.
Digital Torque Tester Suppliers UAE, Exporters Dubai



Equipments Machine UAE

Website: Equipments Machine UAE,