

Email: sales@equipmentsmachinesuae.com

Product Name:

Hydraulic Mobile Car Loading Dock Ramp for Forklift

Product Code: UAEFCE360001



Description:

Hydraulic Mobile Car Loading Dock Ramp for Forklift

Technical Specification:

Loading capacity: 6~15ton.Offer customized service.

Platform size: 1100*2000mm or 1100*2500mm. Offer customized service.

Spillover valve: It can prevent high pressure when the machine moves up. Adjust the pressure. Emergency decline valve: it can go down when you meet an emergency or the power off.

High strength hydraulic support legs will prop up the whole dock ramp stably.

Solid rubber tyre with great wear-proof performance.

Anti-skidding rubber block will stop the mobile dock yard ramp moving when working.

High strength chains will connect the truck or container to the dock yard ramp when working

Load Capacity (t): 8

Platform Size (mm): 11000*2000 Overall Size(mm): 11200*2000*1400

Lip Width (mm): 400

Tail Board Length (mm): 800 Platform Length(mm): 2900 Slope Length(mm): 7500

Adjustable Range of Lifting Height(mm): 900~1700

Operating: Manually

Pit Size (mm): 2080*2040*600

Platform Materials: 4mm checked steel plate +7mm steel screen

Lip Materials: 16mm Q235B plate Lifting Frame: 120×60×4.5 profile steel Bed Frame: 120x60x4.5 profile steel

Lower Truss: 100*50*3 rectangle tube Q235B Guardrails: 60*40*3 rectangle tube Q235B

Tyre: 500-8 solid tyre

Cylinder Pin: 45# Ø50 rod steel*4

Lifting Hydraulic Cylinder: HGS series Ø80/45 Lip Hydraulic Cylinder: HGS series Ø40/25

Hydraulic Oil Pipe: Double wire mesh high pressure tubing 2-10-43MPa

Electrical appliance: Delixi

Hydraulic Oil: antiwear hydraulic oil 6L

Net Weight(kg): 2480 40'container Load Qty: 3sets



Equipments Machine UAE

Website: Equipments Machine UAE,

2/2