

Product Name :	Product Code :		
Stable Upn Structure Hydraulic Dock Ramp	UAEFCE360003		
www.equipmentsmachinesuae.com			
		Description :	
Stable Upn Structure Hydraulic Dock Ramp			
Technical Specification :			
Stationary Dock Yard Ramp is driven by hydraulic pump station and electric motor.			
Loading capacity: 6~15ton.Offer customized service. Platform size: 1100*2000mm or 1100*2500mm. Offer customized service.			
Spillover valve: It can prevent high pressure when the machine moves up. Adjust the pressure.			
Emergency decline valve: it can go down when you meet an emergency or the power off. High strength hydraulic support legs will prop up the whole dock ramp stably.			
Solid rubber tyre with great wear-proof performance.			
Anti-skidding rubber block will stop the mobile dock yard ramp moving when working.			
High strength chains will connect the truck or container to the dock yard ramp when working Load Capacity (t): 6			
Platform Size (mm): 2000*2000/2500			
Lip Width (mm): 400			
Travel Height (mm): Updip 300 Downdip 200			
Motor Power (kw): 0.75			
Pit Size (mm): 2080*2040*600 Platform Materials: 6mm checked steel plate Q235B			
Lip Materials: 14mm Q235B plate			
Lifting Frame: 120×60×6 profile steel			
Bed Frame: 120×60×5 profile steel Shaft Pin: Ø30 steel rod,30×50 welded tube			

Cylinder Support Plate: 12mm Q235B plate Cylinder Pin: 45# Ø50 rod steel*4 Lifting Hydraulic Cylinder: HGS series Ø80/50 Lip Hydraulic Cylinder: HGS series Ø40/25 Hydraulic Oil Pipe: Double wire mesh high pressure tubing 2-10-43MPa Pump Station: Combined type CDK series 0.75KW Electrical appliance: Delixi Hydraulic Oil: antiwear hydraulic oil 6L 40'container Loading Qty: 20sets



Equipments Machine UAE

Website: Equipments Machine UAE,