

Email: sales@equipmentsmachinesuae.com

Product Name:

Stable Upn Structure Hydraulic Dock Ramp

Product Code: UAEFCE360003



Description:

Stable Upn Structure Hydraulic Dock Ramp

Technical Specification:

Stationary Dock Yard Ramp is driven by hydraulic pump station and electric motor.

Loading capacity: 6~15ton.Offer customized service.

Platform size: 1100*2000mm or 1100*2500mm. Offer customized service.

Spillover valve: It can prevent high pressure when the machine moves up. Adjust the pressure.

Emergency decline valve: it can go down when you meet an emergency or the power off.

High strength hydraulic support legs will prop up the whole dock ramp stably.

Solid rubber tyre with great wear-proof performance.

Anti-skidding rubber block will stop the mobile dock yard ramp moving when working.

High strength chains will connect the truck or container to the dock yard ramp when working

Load Capacity (t): 6

Platform Size (mm): 2000*2000/2500

Lip Width (mm): 400

Travel Height (mm): Updip 300

Downdip 200

Motor Power (kw): 0.75

Pit Size (mm): 2080*2040*600

Platform Materials: 6mm checked steel plate Q235B

Lip Materials: 14mm Q235B plate Lifting Frame: 120×60×6 profile steel Bed Frame: 120×60×5 profile steel

Shaft Pin: Ø30 steel rod,30x50 welded tube

Cylinder Support Plate: 12mm Q235B plate

Cylinder Pin: 45# Ø50 rod steel*4

Lifting Hydraulic Cylinder: HGS series Ø80/50 Lip Hydraulic Cylinder: HGS series Ø40/25

Hydraulic Oil Pipe: Double wire mesh high pressure tubing 2-10-43MPa

Pump Station: Combined type CDK series 0.75KW

Electrical appliance: Delixi

Hydraulic Oil: antiwear hydraulic oil 6L 40'container Loading Qty: 20sets



Equipments Machine UAE

Website: Equipments Machine UAE,

2/2