

Email: sales@equipmentsmachinesuae.com

Product Name : Sub-Vertical CIP System

Product Code: UAECIPS0001



Description:

Sub-Vertical CIP System

Technical Specification:

CIP system is one of the prerequisites of food pharmacy production sanitary standards. it can remove the active mixed pollution and insoluble particles of impurity, reduce or remove the micro chemicals and heat source that pollute the productions. GMP requires CIP system in food and pharmacy industry, which limits related industries because the high expense in overseas completely automatically CIP system. The specialists in our company inport and digest international advanced technique, and successfully make automatically CIP system with high automation, simple operation, and reasonable price.

FERFORMANCE CHARACTERISTIC

? Flexiblity And General Usage

The system can undertake single process such as acid cleaning,alkali cleaning,and hot water cleaning,and also can take completely automatic cleaning according to the cleaning process designed. Besides,it can control the growing of micro chemicals.semi-automatic or fully automatic equipments can be made to order.

? Economics And High Effciency

This equipment greatly reduces the cleaning time and increase the work efficiency compared with cleaning by hand; the use of cleaning liquid and water is more reasonable; meanwhile steam cost id relatively small, so to make full use of energy, and reduce the cleaning cost.

? Safety And Reliance

Dense acid liquid and alkali liquid are in the berried acerbity pot and alkali pot;the liquid position is automatically controlled, fixed with overflow protecting system; and unique material outlet construction can stop crystallization

from the cleaning liquid to stop the pipe.

? Matured Plc Controlling System

Years of experience accumulation enhances he programs. Imported qualified controlling part can keep the system operate steadily for along time; friendly interface between people and machine shortens the training time of the operators, and shows directly work condition of key parts of the machine; easily understandable interface can cooperate the operator the make decision, and deal with the common problems, so to ensure the machine return to work in time.

Performance Characteristic

Flexibility And General Usage

The system can undertake single process such as acerbity cleaning, alkali cleaning, and hot water cleaning, and also can take completely automatic cleaning according to the cleaning process designed. Besides, it can control the growing of micro chemicals. Half automatic or complete automatical equipments can be made to order

Safety And Reliance

Dense acerbity liquid and alkali liquid are in the berried acerbity pot and alkali pot; the liquid position is automatically controlled, fixed with overflow protecting system; and unique material outlet construction can stop crystallization from the cleaning liquid to stop the pipe

Economics And High Efficiency

This equipment greatly reduces the cleaning time and increase the work efficiency compared with cleaning by hand; the use of cleaning liquid and water is more reasonable; meanwhile steam cost id relatively small, so to make full use of energy, and reduce the cleaning cost.

Matured PLC Controlling System

Yeats of experience accumulation enhances he programs. Imported qualified controlling part can keep the system operate steadily for along time; friendly interface between people and machine shortens the training time of the operators, and shows directly work condition of key parts of the machine; easily understandable interface can cooperate the operator the make decision, and deal with the common problems, so to ensure the machine return to work in time.

Alkali pot Material 304, conic top and tonic bottom, thickness:

50mm, keeping warm

Material 304, conic top and tonic bottom, thickness: Acerbity pot

50mm,keeping warm

Hot water pot Material 304, conic top and tonic bottom, thickness:

50mm, keeping warm

Material 304, conic top and tonic bottom, thickness: Clean water pot

50mm, keeping warm

Nateruak 316, single layer, plate top and plate bottom Dense acerbity and alkali pot

pot or berried pot

Material 316, flow: 20m³/h, lift: 36m, electric Advancement pump

motor:5.5kw

Material 316, flow: 1000L/h

Plate heat exchanger Material304 Material304

> Material 316,flow: 20m³/h,lift: 20m,electric motor:4kw The shell is stainless; controlling method can be made

to order.

Filter

Returning pump, self-priming pump

Dese acerbity and alkali pump

Steam motored film pump

Controlling cabinet



Equipments Machine UAE

Website: Equipments Machine UAE,

3/3